

# Industry's First 22mm Compact Pilot Devices

## Main Products Include

- Pushbuttons
  - Non-illuminated
    - Momentary Flash Buttons
    - Maintained Flash Buttons
    - Momentary Extend Buttons
    - Maintained Extend Buttons
    - Colors: Red, Green, Yellow, Blue, White, Black, Gray
- Selector Switches
  - Two Position
  - Three Position
  - Colors: Red, Black, and Gray
- Pilot Lights
  - Colors: Red, Green, Yellow, Blue, White, and Clear
- Accessories
  - Bulbs
  - LED's
  - Protective Membranes
  - Mounting Tool
  - Lamp Changing Tool
  - Legend Plates
  - 30mm Adaptor Ring

## Ratings as per UL/CSA/NEMA C300

· Rated Insulation Voltage	250VAC		
· Rated Thermal Current	2.5A		
		Make	Break
· Rated Operational Current	120VAC	15A	1.5A
	240VAC	7.5A	0.75A
· Maximum VA		1800VA	180VA

## Ratings as per UL/CSA/NEMA R300

· Rated Insulation Voltage	250VDC		
· Rated Thermal Current	1A		
		Make	Break
· Rated Operational Current	125VDC	0.22A	0.22A
	250VDC	0.11A	0.11A
· Maximum Make or Break (300V or less)		28VA	28VA